

FAIR-PLAY[®] SCOREBOARDS

CaptiVue[®] Sports Displays



Westlake Village HS | Westlake Village, CA
FB-8132-2 scoreboard
Full-Color CaptiVue display

16 mm (0.625") Amber Outdoor	16 mm (0.625") Full-Color Indoor	16 mm (0.625") Full-Color Outdoor	20 mm (0.787") Full-Color Outdoor	23 mm (0.9") Amber Indoor	23 mm (0.9") Full-Color Indoor	23 mm (0.9") Amber Outdoor	23 mm (0.9") Full-Color Outdoor	35 mm (1.375") Amber Outdoor	35 mm (1.375") Full-Color Outdoor	45 mm (1.75") Amber Outdoor	64 mm (2.5") Amber Outdoor
---------------------------------------	---	--	--	------------------------------------	---	-------------------------------------	--	---------------------------------------	--	--------------------------------------	-------------------------------------

Superior Construction and Engineering:

CaptiVue displays are designed to be integrated into scoreboards and sports timing systems or used as a stand-alone message displays. Power with ProLine to schedule pre-, post- or in-game events and advertising and game time display production control.

- Long life 100,000 hour rated LEDs are up to 90% more efficient than incandescent lamps.
- Aluminum construction provides light-weight, non-corrosive strength while maintaining exacting standards.
- Fair-Play provides detailed installation and operation documentation with every product it sells.
- 100% solid state with quick-service design features.
- ETL and ETL-C certified to UL standard.
- 5-Year Warranty

“When the customer powered up the message center for the first time, they just stood there and looked at it for 15 minutes—it has incredible clarity.”

- Ted Willett, Gulfstream Sports Group, Ft. Lauderdale, FL -

Display Features

Pixel pitch	16mm, (0.625")
Character height	4-inch
Color	1-Red, 1-Blue, 1-Green, 3-LEDs per pixel
Brightness	7,500+ NITS
Anticipated LED life	Up to 100,000 hours
Viewing angle	140° horizontal x 60° vertical
Graphics and animation	ProLine includes FREE animation package and an easy-to-use import feature for JPEG, BMP, GIF, AVI and other common Windows®-type files. Display graphics, animations and video in up to 68-billion colors.
Control system	ProLine for sports applications includes our exclusive Interactive Commander allowing the operator to drag-and-drop animations and messages to display instantly.
Communication options	<ul style="list-style-type: none"> • Direct-wired • Wireless remote (RF) • LAN remote (TCP-IP)
Standard power requirements	120V, single-phase, 60HZ 208V, three-phase, 60HZ
<i>Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.</i>	