

CAPTIONS (H" x W")

HOME	7" x 21"
VISITOR	7" x 29"
PERIOD	4" x 17"
BONUS	4" x 15"
POSS	3" x 9"
FOULS (Personal)	4" x 14"
FOULS (Team)	4" x 14"
PLAYER	4" x 17"
TOL	4" x 10"
NO	4" x 6"
F	4" x 3"
PTS	4" x 8"
POINTS	4" x 16"

DIGIT SIZES (H")

Game Clock	12"
Team Scores	12"
Period	10"
Team Fouls	10"
Player Number	10"
Personal Fouls	10"
Personal Points	10"
Timeouts Left	10"
Stats Fouls	6"
Stats Player	6"
Stats Points	6"

UV resistant custom paint & vinyl trim colors available.

15 Fair-Play FREE Standard Trim Tape Colors

BRIGHT YELLOW	BURGUNDY	BLACK
SUNFLOWER	PURPLE	SILVER METALLIC
BRIGHT ORANGE	LIGHT NAVY	SATN GOLD METALLIC
TOMATO RED	INTENSE BLUE	MEDIUM GRAY
CARDINAL RED	FOREST GREEN	WHITE

12 Fair-Play FREE Standard Scoreboard Colors

BRIGHT RED	KELLY GREEN	REFLEX BLUE
CRIMSON RED	FOREST GREEN	SIGNAL BLACK
DEEP MAROON	CHAMPION BLUE	CHARCOAL
GRAPE PURPLE	ROYAL BLUE	WHITE

MODEL: BB-1766-4



DIMENSIONS

Height	Length	Depth	Weight
5'-0"	18'-0"	4"	360 lbs.

STANDARD EQUIPMENT

- Energy efficient LED designs
- Three distinct LED digit colors to visually organize critical game information
- Heavy-duty, vibrating horn (103 dB)
- 4-level control console display brightness adjustment
- 5-year limited warranty
- Easy access built-in service points
- Quality engineered water resistant aluminum
- Complete, secure and durable display mounting
- Built-in lighting suppressor (for standard data direct wire only)
- Request a free project design renderings
- Help Desk Support
- USA Factory authorized national and local sales, service and installation

OPTIONAL EQUIPMENT

- Full-color electronic message displays
- Integrated scoring and display systems
- Illuminated, non-illuminated identification and sponsorship signage
- Personalized vinyl home team name
- Scoreboard caption color (other than white)
- Custom, unique signage options
- Scoreboard control carrying case
- Truss and decorative steel systems
- Power lighting protector or protective net
- Count side tables options in 8ft, 10ft or 7.7ft long configured with front BB scoreboard
- Synchronized locker room game / time of day clocks
- Protective net

ELECTRICAL

Voltage	Hertz	Watts	AMPS	Phase	Wiring	Circuits Required	Safety Listing	Scoreboard Display	Control Console
120 VAC	60	373	3.11	1	2-Wire + ground	1	ETL/CETL	-22° to 131° F	-30° to 55° C
								32° to 131° F	0° to 55° C

OPERATING TEMPERATURES

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.

For applicable models, consult with a sales representative on the following:

- Choice of Fair-Play's scorekeeper approved score systems
- Electronic Team Names
- Rear-illuminated scoreboard captions or scoreboard sport-conversion captions (electronic)
- Changeable scoreboard game captions — electronic available, operated via control
- Integrated, second operator statistics control