



HK-1670-4

HK-1670-4

SIZE: 9'-0"L X 6'-0"H X 4"D

POWER: 120 VAC, 60 Hz., 1-PHASE
203 WATTS.

120 VAC AT THE CONTROL LOCATION.

CONTROL CONSOLE: MP-70 SERIES CONTROLLER.
CONTROL CABLE: 22GA 2-WIRE SHIELDED.

LED'S: LED BAR.

OPTIONS: MODEL HH-70 CLOCK HAND SWITCH FOR SECOND OPERATOR.
(CLOCK START/STOP & MANUAL HORN.)

MODEL HC-70 CLOCK HAND SWITCH FOR SECOND OPERATOR.
(CLOCK START/ STOP & CLOCK RESET.)

ESTIMATED WEIGHT: 270 LBS.

GENERAL NOTES:

- * REFERENCE 01-0500-01 FOR INSTALLATION NOTES.
- * POWER REQUIREMENTS ARE VALID FOR 90 DAYS AFTER THE ORIGINAL RELEASE OR BY THE MOST RECENT REVISION OF THE DRAWING.

FAIR-PLAY

6110 AVIATOR DRIVE
HAZELWOOD, MO 63042
fair-play.com

PROJECT NAME:		REF. #:	
THIS DOCUMENT CONTAINS TRANS-LUX PROPRIETARY INFORMATION. ANY DISCLOSURE, USE OR DUPLICATION OF THE DOCUMENT OR OF ANY INFORMATION CONTAINED THEREIN FOR OTHER THAN THE SPECIFIC PURPOSE FOR WHICH IT WAS DEVELOPED IS EXPRESSLY PROHIBITED, EXCEPT AS MAY BE OTHERWISE AGREED TO IN WRITING. COPYRIGHT 2010.			
TITLE	DRAWN BY	DATE	MODEL:
FACE VIEW FOR HK-1670-4	BEW	B	HK-1670-4
	08-14-12		DWG. NO.
	SCALE		01-1670-06-1
	1/2" = 1'-0"		

OR	ORIGINAL RELEASE	08-14-12	BEW
REV.#	CHANGE	DATE	BY