

CAPTIONS (H" x W")

| | |
|-------|----------|
| HOME | 4" x 13" |
| GUEST | 4" x 15" |

DIGIT SIZES (H")

| | |
|---------|-----|
| Home | 10" |
| Guest 1 | 10" |

MODEL: SW-1541-4



DIMENSIONS

| Height | Length | Depth | Weight |
|--------|--------|-------|---------|
| 1'-0" | 7'-0" | 4" | 38 lbs. |

UV resistant custom paint & vinyl trim colors available.

12 Fair-Play FREE Standard Scoreboard Colors

| | | |
|--------------|---------------|--------------|
| | | |
| BRIGHT RED | KELLY GREEN | REFLEX BLUE |
| | | |
| CRIMSON RED | FOREST GREEN | SIGNAL BLACK |
| | | |
| DEEP MAROON | CHAMPION BLUE | CHARCOAL |
| | | |
| GRAPE PURPLE | ROYAL BLUE | WHITE |

STANDARD EQUIPMENT

- Energy efficient LED designs
- Three distinct LED digit colors to visually organize critical game information
- Heavy-duty, vibrating horn (103 dB)
- 4-level control console display brightness adjustment
- 5-year limited warranty
- Easy access built-in service points
- Quality engineered water resistant aluminum
- Complete, secure and durable display mounting
- Built-in lighting suppressor (for standard data direct wire only)
- Request a free project design renderings
- Help Desk Support
- USA Factory authorized national and local sales, service and installation

OPTIONAL EQUIPMENT

- Full-color electronic message displays
- Integrated scoring and display systems
- Illuminated, non-illuminated identification and sponsorship signage
- Personalized vinyl home team name
- Scoreboard caption color (other than white)
- Custom, unique signage options
- Scoreboard control carrying case
- Truss and decorative steel systems
- Power lighting protector or protective net

ELECTRICAL

| Voltage | Hertz | Watts | AMPS | Phase | Wiring | Circuits Required | Safety Listing | Scoreboard Display | Control Console |
|---------|-------|-------|------|-------|-----------------|-------------------|----------------|--------------------------------|-----------------------------|
| 120 VAC | 60 | 40 | 1 | 1 | 2-Wire + ground | 1 | ETL/CETL | -22° to 131° F -30° to 55° C | 32° to 131° F 0° to 55° C |

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.

OPERATING TEMPERATURES

For applicable models, consult with a sales representative on the following:

- Choice of Fair-Play's scorekeeper approved score systems
- Electronic Team Names
- Rear-illuminated scoreboard captions or scoreboard sport-conversion captions (electronic)
- Changeable scoreboard game captions — electronic available, operated via control
- Integrated, second operator statistics control