

15"

CAPTIONS (H" x W")

Colon Diameter 2.16"

DIGIT SIZES (H")

Game Clock

MODEL: CL-1020-2



STANDARD EQUIPMENT

- Super-bright, wide-angle amber LED's
- 4-level control console display brightness adjustment
- 5-year limited warranty ٠
- Easy access built-in service points ٠
- Quality engineered water resistant aluminum .
- Complete, secure and durable display mounting
- Built-in lighting suppressor (for standard data . direct wire only)
- Request a free project design renderings ٠
- Help Desk Support .
- USA Factory authorized national and local sales, service and installation

OPTIONAL EQUIPMENT

- Full-color electronic message displays
- Integrated scoring and display systems
- Illuminated, non-illuminated identification • and sponsorship signage
- Custom, unique signage options ٠
- Scoreboard control carrying case ٠

Protective net ٠

Please see Color Chart PDF for all scoreboard color options.

UV resistant custom paint & vinyl trim colors available.

ELECTRICAL								OPERATING TEMPERATURES			
Voltage	Hertz	Watts	AMPS	Phase	Wiring	Circuits Required	Safety Listing	Clock Display		Control Console	
120 VAC	60	53	0.48	1	2-Wire + ground	1	ETL/CETL/UL	-22° to 131° F	-30° to 55° C	32° to 131° F	0° to 55° C

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.