

OUTDOOR TRACK & FIELD SCOREBOARD

SPECIFICATIONS

CAPTIONS (H" x W")

LANE PLACE 4" x 15" TIME 4" x 11" Decimal 1.75" 1.75" **Colon Diameter**

DIGIT SIZES (H")

Lane	12"
Place	12"
Time	12"

MODEL: TK-1504-2



DIMENSIONS	Height	Length	Depth	Weight
	3'-6"	16'-0"	10"	392 lbs.

STANDARD EQUIPMENT

- Super-bright, wide-angle amber LED's
- 4-level control console display brightness adjustment
- 5-year limited warranty
- Easy access built-in service points
- Quality engineered water resistant aluminum
- Complete, secure and durable display mounting
- Built-in lightning suppressor (for standard data direct wire only)
- Request a free project design renderings
- Help Desk Support
- USA Factory authorized national and local sales, service and installation

OPTIONAL EQUIPMENT

- Full-color electronic message displays
- Integrated scoring and display systems
- Illuminated, non-illuminated identification and sponsorship signage
- Personalized vinyl home team name
- Scoreboard caption color (other than white)
- Custom, unique signage options
- Scoreboard control carrying case
- Truss and decorative steel systems
- Power lighting protector or protective net

Please see Color Chart PDF for all scoreboard color options. UV resistant custom paint &

vinyl trim colors available.

ELECTRICAL

OPERATING TEMPERATURES

120 VAC 60 422 9 1 2-Wire + ground 1 ETL/CETL -22° to 131° F -30° to 55° C 32° to 131° F 0° to 55° C	Voltage	Hertz	Watts	AMPS	Phase	Wiring	Circuits Required	Safety Listing	Scoreboard Disp	lay	Control Console	;
	120 VAC	60	422	9	1	2-Wire + ground	1	ETL/CETL	-22° to 131° F	-30° to 55° C	32° to 131° F	0° to 55° C

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.

For applicable models, consult with a sales representative on the following:

- Choice of Fair-Play's scorekeeper approved score systems
- Electronic Team Names
- Rear-illuminated scoreboard captions or scoreboard sport-conversion captions (electronic)
- Changeable scoreboard game captions electronic available, operated via control
- Integrated, second operator statistics control