

CAPTIONS (H" x W")

HOME 11" x 39" **VISITOR** 11" x 50" 11" x 36" BALL ON 11" x 29" DOWN TO GO 11" x 29" QTR 11" x 20" TOL 8" x 16" **Colon Diameter**

DIGIT SIZES (H")

Ball On (or On)	24"
Game Clock	24"
Team Scores	24"
To Go	24"
Down	24"
Qtr	18"
Timeouts Left	15"

MODEL: FB-8318-2



DIMENSIONS	Height	Length	Depth	Weight	
	7'-6"	18'-0"	10"	575 lbs.	

STANDARD EQUIPMENT

- Super-bright, wide-angle amber LED design
- 4-level control console display brightness adjustment
- 5-year limited warranty
- Easy access built-in service points
- Quality engineered water resistant aluminum
- Complete, secure and durable display mounting
- Built-in lightning suppressor (for standard data direct wire only)
- Request a free project design renderings
- Help Desk Support
- USA Factory authorized national and local sales, service and installation

OPTIONAL EQUIPMENT

- Full-color electronic message displays
- Integrated scoring and display systems
- Illuminated, non-illuminated identification and sponsorship signage
- Personalized vinyl home team name
- Scoreboard caption color (other than white)
- Custom, unique signage options
- Scoreboard control carrying case
- Truss and decorative steel systems

OPERATING TEMPERATURES

- Field use time
- Power lighting protector or protective net

Please see Color Chart PDF for all scoreboard color options.

UV resistant custom paint & vinyl trim colors available.

ELECTRICAL

Voltage	Hertz	Watts	AMPS	Phase	Wiring	Circuits Required		Si
120 VAC	60	576	5	1	2-Wire + ground	1	ETL/CETL	-2

Ī	Scoreboard Display		Control Console		
_	-22° to 131° F	-30° to 55° C	32° to 131° F	0° to 55° C	

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.

For applicable models, consult with a sales representative on the following:

- Choice of Fair-Play's scorekeeper approved score systems
- Electronic Team Names
- Rear-illuminated scoreboard captions or scoreboard sport-conversion captions (electronic)
- Changeable scoreboard game captions electronic available, operated via control
- Integrated, second operator statistics control