

FB-8132TKH-2

SIZE: 32'-0" L X 8'-0" H X 10" D

POWER: 120 VAC, 60 Hz., 1-PHASE
782 WATTS.

120 VAC AT THE CONTROL LOCATION.

CONTROL CONSOLE: MP-70 SERIES CONTROLLER.
CONTROL CABLE: 22GA 2-WIRE SHIELDED.
(IF WIRELESS ORDERED, NO CABLE REQ'D.)

LEDs: AMBER LED.

OPTIONS: MODEL HC-70 CLOCK HAND SWITCH FOR SECOND OPERATOR.
(CLOCK START/STOP & CLOCK RESET.)


MODEL F600-70 SIDELINE CLOCK HAND SWITCH CONTROL
WITH SPLIT TIME.

MODEL F650-70 SIDELINE CLOCK HAND SWITCH CONTROL.
LIGHTNING DAMAGE REDUCTION UNIT.

WIRELESS MP-70 CONTROL OPERATION.

ESTIMATED WEIGHT: 1,100 LBS.

GENERAL NOTES:
* REFERENCE 01-0500-01 FOR INSTALLATION NOTES.
* POWER REQUIREMENTS ARE VALID FOR 90 DAYS AFTER THE ORIGINAL
RELEASE OR BY THE MOST RECENT REVISION OF THE DRAWING.



FB-8132TKH-2

CUSTOMER APPROVAL:		MY SIGNATURE BELOW SIGNIFIES MY APPROVAL TO PROCEED WITH THE DESIGN WORK SPECIFIED HEREIN AND ACKNOWLEDGEMENT THAT I HAVE RECEIVED AND READ THE INSTALLATION SPECIFICATIONS CONTAINED IN FAIR-PLAY DOCUMENT NO. 01-0500-01. CONSULT YOUR FAIR-PLAY SALES ASSOCIATE IF YOU SHOULD HAVE ANY QUESTIONS OR REQUIRE ANY CHANGES TO THIS DOCUMENT.	
PROJECT:	SIGNATURE:	DATE:	
REFERENCE #:	PRINT NAME:		

FAIR-PLAY 6110 AVIATOR DRIVE HAZELWOOD, MO 63042	THIS DOCUMENT CONTAINS FAIR-PLAY PROPRIETARY INFORMATION. ANY DISCLOSURE, USE OR DUPLICATION OF THE DOCUMENT OR OF ANY INFORMATION CONTAINED THEREIN FOR OTHER THAN THE SPECIFIC PURPOSE FOR WHICH IT WAS DISCLOSED IS EXPRESSLY PROHIBITED, EXCEPT AS MAY BE OTHERWISE AGREED TO IN WRITING. COPYRIGHT 2022.	
	TITLE	MODEL
	FACE VIEW FOR FB-8132TKH-2	B FB-8132TKH-2
	DATE 06-17-09	DWG. NO. 01-8132-104-1
	DRAWN BY RMS	
	SCALE 1/4"=1'-0"	

REV.#	CHANGE	DATE	BY
B	UPDATED TITLE BLOCK FORMAT	08-16-22	BEW
A	UPDATED FORMAT, ADDED POWER NOTE	04-10-12	BEW
OR	ORIGINAL RELEASE	06-17-09	RMS