

SC-8120-2

 D
 UPDATED TITLE BLOCK FORMAT
 09-02-22 BEW

 C
 GENERAL UPDATES, ADDED POWER NOTE
 04-17-12 BEW

 B
 GENERAL UPDATES
 05-09-11 BEW

 A
 GENERAL UPDATES
 10-01-07 BEW

 OR
 ORIGINAL RELEASE
 10-27-06 BEW

 REV.#
 CHANGE
 DATE
 BY

SC-8120-2

SIZE: 20'-0"L X 7'-6"H X 10"D

POWER: 120 VAC, 60 Hz., 1-PHASE

509 WATTS.

120 VAC AT THE CONTROL LOCATION.

CONTROL CONSOLE: MP-70 SERIES CONTROLLER.

CONTROL CABLE: 22GA 2-WIRE SHIELDED.

(NO CABLE REQ'D. IF ORDERED WIRELESS.)

LEDs: AMBER LED.

OPTIONS: MODEL HC-70 CLOCK HAND SWITCH FOR SECOND OPERATOR. (CLOCK START/STOP & CLOCK RESET.)

MODEL F600-70 SIDELINE CLOCK HAND SWITCH CONTROL

WITH SPLIT TIME.

MODEL F650-70 SIDELINE CLOCK HAND SWITCH CONTROL.

LIGHTNING DAMAGE REDUCTION UNIT.

OPTIONAL WIRELESS MP-70 OPERATION.

ESTIMATED WEIGHT: 750 LBS.

## **GENERAL NOTES:**

- \* REFERENCE 01-0500-01 FOR INSTALLATION NOTES.
- \* POWER REQUIREMENTS ARE VALID FOR 90 DAYS AFTER THE ORIGINAL RELEASE OR BY THE MOST RECENT REVISION OF THE DRAWING.

CUSTOMER APPROVAL: THAVE		E DESIGN WORK SPECIFIED HEREIN AND ACKNOWLEDGEMENT THAT UNED IN FAIR-PLAY DOCUMENT NO. 01-0500-01. CONSULT YOUR DR REQUIRE ANY CHANGES TO THIS DOCUMENT.
PROJECT:	SIGNATURE:	DATE:
REFERENCE #:	PRINT NAME:	

FΔ	R-D	LΔY

6110 AVIATOR DRIVE HAZELWOOD, MO 63042 THIS DOCUMENT CONTAINS FAIR-PLAY PROPRIETARY INFORMATION. ANY DISCLOSURE, USE OR DUPLICATION OF THE DOCUMENT OR OF ANY INFORMATION CONTAINED THEREIN FOR OTHER THAN THE SPECIFIC PURPOSE FOR WHICH IT WAS DISCLOSED IS EXPRESSLY PROHIBITED, EXCEPT AS MAY BE OTHERWISE AGREED TO IN WRITING. COPYRIGHT 2022.

FACE VIEW FOR SC-8120-2