## CAPTIONS (H" x W")

| HOME           | 15" x 60" |
|----------------|-----------|
| VISITOR        | 15" x 79" |
| DOWN           | 18" x 48" |
| TO GO          | 18" x 53" |
| ON             | 18" x 22" |
| QTR            | 18" x 29" |
| TOL            | 10" x 22" |
| Colon Diameter | 3"        |
|                |           |

#### DIGIT SIZES (H")

| Game Clock      | 30" |
|-----------------|-----|
| Ball On (or On) | 24" |
| Team Scores     | 24" |
| To Go           | 24" |
| Down            | 24" |
| Qtr             | 24" |
| Timeouts Left   | 18" |
| Possession      | 10" |
|                 |     |

# MODEL: FB-8126TK



| noight | Longin | ••• | J . J .    |
|--------|--------|-----|------------|
| 8'-0"  | 26'-0" | 10" | 1,105 lbs. |
|        |        |     |            |

#### OPTIONAL EQUIPMENT

- Full-color electronic message displays
- Integrated scoring and display systems
- Illuminated, non-illuminated identification and sponsorship signage
- Personalized vinyl home team name
- Scoreboard caption color (other than white)
- Custom, unique signage options
- Scoreboard control carrying case
- Truss and decorative steel systems
- Field use time
- Power lightning protector or protective net

### ELECTRICAL

STANDARD EQUIPMENT

5-year limited warranty

adjustment

direct wire only)

Help Desk Support

sales, service and installation

٠

٠

٠

• Super-bright, wide-angle amber LED design

4-level control console display brightness

Quality engineered water resistant aluminum

Complete, secure and durable display mounting

Built-in lightning suppressor (for standard data

Request a free project design rendering

USA Factory authorized national and local

Easy access built-in service points

#### OPERATING TEMPERATURES

| Voltage | Hertz | Watts | AMPS | Phase | Wiring          | Circuits<br>Required | Safety<br>Listing | Scoreboard Display |               | Control Console |                           |
|---------|-------|-------|------|-------|-----------------|----------------------|-------------------|--------------------|---------------|-----------------|---------------------------|
| 120 VAC | 60    | 731   | 7    | 1     | 2-Wire + ground | 1                    | ETL/CETL          | -22° to 131° F     | -30° to 55° C | 32° to 131° F   | $0^\circ$ to $55^\circ$ C |

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.

#### For applicable models, consult with a sales representative on the following:

- Choice of Fair-Play's scorekeeper approved score systems
- Electronic Team Names
- Rear-illuminated scoreboard captions or scoreboard sport-conversion captions (electronic)
- Changeable scoreboard game captions electronic available, operated via control
- Integrated, second operator statistics control

| Please see Color Chart PDF for |  |
|--------------------------------|--|
| all scoreboard color options.  |  |

UV resistant custom paint & vinyl trim colors available.