

CAPTIONS (H" x W")

| | |
|---------|----------------|
| HOME | 8" x 48 1.375" |
| VISITOR | 8" x 48 1.375" |
| DOWN | 8" x 22" |
| TO GO | 8" x 21" |
| BALL ON | 8" x 31" |
| QTR | 8" x 15" |
| TOL | 6" x 13" |

DIGIT SIZES (H")

| | |
|-----------------|-----|
| Game Clock | 24" |
| Team Scores | 24" |
| To Go | 18" |
| Ball On (or On) | 18" |
| Down | 18" |
| Qtr | 18" |
| Timeouts Left | 15" |
| Possession | 10" |
| Colon Diameter | 3" |

MODEL: FB-3248-48L



DIMENSIONS

| Height | Length | Depth | Weight |
|--------|--------|-------|----------|
| 4'-0" | 32'-0" | 10" | 544 lbs. |

STANDARD EQUIPMENT

- Super-bright, wide-angle amber LED design
- 4-level control console display brightness adjustment
- 5-year limited warranty
- Easy access built-in service points
- Quality engineered water resistant aluminum
- Complete, secure and durable display mounting
- Built-in lightning suppressor (for standard data direct wire only)
- Request a free project design rendering
- Help Desk Support
- USA Factory authorized national and local sales, service and installation

OPTIONAL EQUIPMENT

- Full-color electronic message displays
- Integrated scoring and display systems
- Illuminated, non-illuminated identification and sponsorship signage
- Personalized vinyl home team name
- Scoreboard caption color (other than white)
- Custom, unique signage options
- Scoreboard control carrying case
- Truss and decorative steel systems
- Field use time
- Power lightning protector or protective net

Please see Color Chart PDF for all scoreboard color options.

UV resistant custom paint & vinyl trim colors available.

ELECTRICAL

| Voltage | Hertz | Watts | AMPS | Phase | Wiring | Circuits Required | Safety Listing | Scoreboard Display | Control Console |
|---------|-------|-------|------|-------|-----------------|-------------------|----------------|--------------------------------|-----------------------------|
| 120 VAC | 60 | 942 | 8 | 1 | 2-Wire + ground | 1 | ETL/CETL | -22° to 131° F -30° to 55° C | 32° to 131° F 0° to 55° C |

OPERATING TEMPERATURES

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.

For applicable models, consult with a sales representative on the following:

- Choice of Fair-Play's scorekeeper approved score systems
- Electronic Team Names
- Rear-illuminated scoreboard captions or scoreboard sport-conversion captions (electronic)
- Changeable scoreboard game captions — electronic available, operated via control
- Integrated, second operator statistics control

For orders and questions:
sales@fair-play.com

FAIRPLAY CORPORATION 800.247.0265 • fair-play.com
Nearly a Century of Scoring Experience 6110 Aviator Drive, Hazelwood, MO 63042