

### CAPTIONS (H" x W")

|                 |           |
|-----------------|-----------|
| HOME            | 12" x 45" |
| VISITOR         | 12" x 52" |
| TOTAL           | 7" x 26"  |
| 1               | 7" x 4"   |
| 2,3,4,5,6,7,8,9 | 7" x 5"   |
| BALL            | 9" x 26"  |
| STRIKE          | 9" x 36"  |
| OUT             | 9" x 21"  |
| AT BAT-TIME     | 9" x 31"  |

### DIGIT SIZES (H")

|               |     |
|---------------|-----|
| BALL SPOT     | 18" |
| AT BAT        | 18" |
| OUT SPOT      | 18" |
| STRIKE SPOT   | 18" |
| INNING SCORES | 15" |
| TOTAL         | 15" |

### MODEL: BA-7120MP



### DIMENSIONS

| Height | Length | Depth | Weight   |
|--------|--------|-------|----------|
| 6'-6"  | 20'-0" | 10"   | 649 lbs. |

### STANDARD EQUIPMENT

- Super-bright, wide-angle amber LED's
- 4-level control console display brightness adjustment
- 5-year limited warranty
- Easy access built-in service points
- Quality engineered water resistant aluminum
- Complete, secure and durable display mounting
- Built-in lightning suppressor (for standard data direct wire only)
- Request a free project design rendering
- Help Desk Support
- USA Factory authorized national and local sales, service and installation

### OPTIONAL EQUIPMENT

- Full-color electronic message displays
- Integrated scoring and display systems
- Illuminated, non-illuminated identification and sponsorship signage
- Personalized vinyl home team name
- Scoreboard caption color (other than white)
- Custom, unique signage options
- Scoreboard control carrying case
- Truss and decorative steel systems
- Power lightning protector

Please see Color Chart PDF for all scoreboard color options.

UV resistant custom paint & vinyl trim colors available.

### ELECTRICAL

| Voltage | Hertz | Watts | AMPS | Phase | Wiring          | Circuits Required | Safety Listing | Scoreboard Display | Control Console |
|---------|-------|-------|------|-------|-----------------|-------------------|----------------|--------------------|-----------------|
| 120 VAC | 60    | 379   | 1    | 1     | 2-Wire + ground | 1                 | UL             | -22° to 131° F     | -30° to 55° C   |

### OPERATING TEMPERATURES

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.

### For applicable models, consult with a sales representative on the following:

- Choice of Fair-Play's scorekeeper approved score systems
- Electronic Team Names
- Rear-illuminated scoreboard captions or scoreboard sport-conversion captions (electronic)
- Changeable scoreboard game captions — electronic available, operated via control
- Pitch Speed or Pitch Count Display Systems