

### CAPTIONS (H" x W")

|                |           |
|----------------|-----------|
| HOME           | 11" x 39" |
| VISITOR        | 11" x 50" |
| DOWN           | 13" x 34" |
| TO GO          | 13" x 34" |
| QTR            | 13" x 24" |
| Colon Diameter | 3"        |

### DIGIT SIZES (H")

|             |     |
|-------------|-----|
| Game Clock  | 24" |
| Team Scores | 24" |
| To Go       | 24" |
| Down        | 24" |
| Qtr         | 18" |

### MODEL: FB-8218TK



### DIMENSIONS

| Height | Length | Depth | Weight   |
|--------|--------|-------|----------|
| 7'-6"  | 18'-0" | 10"   | 575 lbs. |

### STANDARD EQUIPMENT

- Super-bright, wide-angle amber LED design
- 4-level control console display brightness adjustment
- 5-year limited warranty
- Easy access built-in service points
- Quality engineered water resistant aluminum
- Complete, secure and durable display mounting
- Built-in lightning suppressor (for standard data direct wire only)
- Request a free project design rendering
- Help Desk Support
- USA Factory authorized national and local sales, service and installation

### OPTIONAL EQUIPMENT

- Full-color electronic message displays
- Integrated scoring and display systems
- Illuminated, non-illuminated identification and sponsorship signage
- Personalized vinyl home team name
- Scoreboard caption color (other than white)
- Custom, unique signage options
- Scoreboard control carrying case
- Truss and decorative steel systems
- Field use time
- Power lightning protector or protective net

Please see Color Chart PDF for all scoreboard color options.

UV resistant custom paint & vinyl trim colors available.

### ELECTRICAL

| Voltage | Hertz | Watts | AMPS | Phase | Wiring          | Circuits Required | Safety Listing | Scoreboard Display | Control Console |
|---------|-------|-------|------|-------|-----------------|-------------------|----------------|--------------------|-----------------|
| 120 VAC | 60    | 533   | 5    | 1     | 2-Wire + ground | 1                 | UL             | -22° to 131° F     | -30° to 55° C   |

### OPERATING TEMPERATURES

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.

### For applicable models, consult with a sales representative on the following:

- Choice of Fair-Play's scorekeeper approved score systems
- Electronic Team Names
- Rear-illuminated scoreboard captions or scoreboard sport-conversion captions (electronic)
- Changeable scoreboard game captions — electronic available, operated via control
- Integrated, second operator statistics control